




UCCONNECT®

UC Copper Patchcord Dual Boot

Cat.5e Dual Boot U/UTP 24AWG 100 MHz, Stranded Copper Patchcord



Stranded bare copper conductors insulated with thermoplastics polyolefin. Two insulated conductors twisted together to form a pair and four such pairs cabled to form the basic unit. Overall jacket with LSZH/PVC compound.

Specification

| Item | |
|-------------------|--|
| Conductor | |
| Size | 24AWG |
| Туре | Stranded bare copper |
| Diameter | 7/0.19±0.01 mm |
| Insulation | |
| Туре | Solid PE |
| Diameter | 0.93±0.05 mm |
| Min. thickness | 0.15 mm |
| Pairs | |
| Color | Blue/White, Orange/White, Green/White, Brown/White |
| Jacket | |
| Туре | LSZH/PVC |
| Overall Diameter | 5.0±0.3 mm |
| Avg. thickness | 0.52 mm |
| Min. thickness | 0.47 mm |
| Assembly | |
| RJ45 Modular Plug | 50 u gold plated contact |



UCCONNECT®

UC Copper Patchcord Dual Boot

Termination Coding TIA 568-B

Plug Housing UL94V-0 rated clear polycarbonate

Boot Unique dual boot design to maximize cable latch

protection

Flame retardant LSZH: IEC60754-1&2; IEC61034

PVC: IEC60332-1

Cable Marking

Draka UC CONNECT DBOOT Cat.5e U/UTP < Jacket Type> < PN> 24AWG EN 50288 ISO/IEC 11801 2nd ed. WW/YYYY < Batch Code> < FC>

<Jacket Type>: LSZH/PVC
<PN>: PC5110 or PC5120
WW/YYYY: Week/Year

<Batch Code>: Factory defined tracking code

<FC>: Draka defined factory code

Ordering Information

The PN of the Dual Boot Cat.5e U/UTP LSZH/PVC are configured based on the table below:

| PATCHCORD | PATCHCORD TYPE | COLOR | | LENGTH |
|-----------|------------------------------------|-------------|---|----------|
| PC | XX | XX | - | XX |
| | 5110 – Dual Boot Cat.5e U/UTP PVC | GY – Grey | | 1 = 1m |
| | 5120 – Dual Boot Cat.5e U/UTP LSZH | GN – Green | | 0 = 1.5m |
| | | YL – Yellow | | 2 = 2m |
| | | RD – Red | | 5 = 5m |
| | | BL – Blue | | 20 = 20m |

Example of a Dual Boot copper patchcord part number:

PC5120GY-1: Dual Boot copper patchcord Cat.5e U/UTP LSZH in 1 metre length with grey color

Enquiries

Please contact our local sales office or mms.asia@prysmiangroup.com

Multimedia Solutions is the data communication portfolio of Prysmian Group and comprises all the necessary portfolio of cable solutions for data communication.

Ask about UC CONNECT for a complete Structure Cabling Solutions with 25 Years System Warranty.

 $\label{eq:visit_www.DrakaUC.com} \ \text{for more information}.$

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

[©] PRYSMIAN GROUP 2017, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.